



## LEDLINE SLD4000TC/MP - 40W

LED diffused batten 40 watt with selectable power and CCT

### Application

Conventional LED linear surface mount batten for commercial service spaces

### Design Specifications

- Robust, pressed steel body profile
- White powder coat finish with an opal PMMA diffuser
- High efficiency LED optics, CRI > 80
- Integral flickerCONTROLLED non-dimmable LED driver 40 watt as standard, optional dimming, emergency and sensor functions available.
- Default (maximum) current selection is 1000mA, refer installation sheet for optional range selections
- Unique diffuser design allows end to end installation and large terminal block for easy installation



### Performance

- Dimmable - **OPTIONAL**
- Dimmer Type - **Trailing edge, 1-10V, DALI / DSI**
- In Built Sensor - **OPTIONAL**
- Sensor Type - **MICROWAVE**



### Technical Specification

Product	Model No.	Input Voltage (V/AC)	Power (W)	Lumens (lm)	CCT (K)	CRI
	SLD4000TC/MP	240	40	4500/4800/4600	3000/4000/5700	80
Beam Angle (°)	Dimmable	Dim (mm)	Body Colour			
110	OPTIONAL	1120(L) x 100(W) x 77(H)	WHITE			

Due to continued product and technology enhancements, data sourced from sal.net.au shall not form part of any contract and or technical performance guarantee unless expressly confirmed in writing by SAL at the time of order. Products are sold in accordance with SAL Terms and Conditions of sale and all images shown are for illustration purposes only and may vary from the actual colour or finish. Unless specifically stated, all IP ratings nominated for Interior products are from "below the ceiling".



## Dimensions

