



LT SERIES LT409MP/TC - 3/6/9W

9 watt, non-dimmable LED tubular lamps with selectable CCT and power

Application

Energy efficient LED lamp solutions for residential spaces

Design Specifications

- Opal polycarbonate diffuser
- Poly covered aluminium body
- High efficiency LED optics, CRI >80, beam distribution 200°
- Integral flickerCONTROLLED non-dimmable LED driver with selectable power 3/6/9watt
- Selectable CCT 3000K / 4000K / 6000K
- Suits most traditional CFL lamp fittings, lamp bases B22, E27



Performance

- Dimmable - NO





Technical Specification

Product	Model No.	Input Voltage (V/AC)	Multiple Wattage	Lumens (lm)	CCT (K)	CRI
	LT409MP/TC/B22	240	3/6/9 watts	300/600/900	3000/4000/6000	80
	LT409MP/TC/E27	240	3/6/9 watts	300/600/900	3000/4000/6000	80

Beam Angle (°)	Dimmable	Diameter (mm)	Length (mm)	Base Type
200	NO	40	105	B22
200	NO	40	105	E27

IMPORTANT: (1) lumens displayed are at the 4000K setting of 3/6/9watt, (2) where CCT or power selection switching is provided, it is important to switch OFF the SUPPLY before the CCT or power selection is made, otherwise equipment damage may occur.

Due to continued product and technology enhancements, data sourced from sal.net.au shall not form part of any contract and or technical performance guarantee unless expressly confirmed in writing by SAL at the time of order. Products are sold in accordance with [SAL Terms and Conditions of sale](#) and all images shown are for illustration purposes only and may vary from the actual colour or finish. Unless specifically stated, all IP ratings nominated for Interior products are from "below the ceiling".

COLOUR TEMPERATURE, THERE IS A DIFFERENCE



TC SELECTABLE COLOUR		
WARM WHITE 2700K	COOL WHITE 4000K	DAYLIGHT 6000K

Lighting is more than just brightness or lumens. Make sure you take the time to select the right colour temperature to create the best visual appearance; your eyes don't tell lies!