




# LED DIRECTIONAL MR16 LAMP

## MR16 5W, MR16 7W, MR16 DIM9W



### DIMENSIONS



### CONSTRUCTION

- Shockproof frosted polycarbonate lens
- Poly covered aluminium body (MR16 5W)
- Die-cast aluminium body (MR16 7W, MR16DIM9W)
- High efficiency SMD LED chips
- 12V AC or DC driver required

### FEATURES

- Directly replace MR16 halogen lamp
- Compatible with all leading brand electronic transformers
- Suits most halogen MR16 fittings

### COLOUR TEMPERATURE

- 3000K Warm White
- 6000K Daylight

### LAMP BASE

- GU5.3

Model No.	Input	Power	Lumen	CCT	Beam Angle	CRI	Dimmable	Lamp Base
MR16 5W WW	12V AC or DC	5W	330lm	3000K	38°	>80	No	GU5.3
MR16 5W DL	12V AC or DC	5W	350lm	6000K	38°	>80	No	GU5.3

Model No.	Input	Power	Lumen	CCT	Beam Angle	CRI	Dimmable	Lamp Base
MR16/7W/WW	12V AC or DC	7W	500lm	3000K	60°	>80	No	GU5.3
MR16/7W/DL	12V AC or DC	7W	550lm	6000K	60°	>80	No	GU5.3

Model No.	Input	Power	Lumen	CCT	Beam Angle	CRI	Dimmable	Lamp Base
MR16DIM9W/WW	12V AC or DC	9W	500lm	3000K	60°	>80	Yes*	GU5.3
MR16DIM9W/DL	12V AC or DC	9W	550lm	6000K	60°	>80	Yes*	GU5.3

\*Trailing edge dimming