



NEWMAN IV S9525TC - 12W / 35W

Retractable & rotatable LED Shoplight, with selectable CCT, selectable power and dimming options

Application

Ideal for any retail or commercial interior space

Design Specifications

- Durable die-cast aluminium body profile in three convenient sizes
- Stylish white powder coat finish
- Optimum tilting function 340° horizontal plane, 60° vertical plane
- High output LED optics, 36° beam distribution with a multi-faceted reflector system
- Selectable CCT 2700/4000/6000K
- Remote, flickerCONTROLLED LED driver with flex and plug and optional dimming and selectable power functions - 12 watt dimmable only or 15/20/25 watt or 25/30/35 watt with non-dimmable and selectable power functions.






Performance

- Dimmable - **OPTIONAL**
- Dimmer Type - **Trailing edge, 1-10V, DALI / DSI**





Technical Specification

Product	Model No.	Input Voltage (V/AC)	Multiple Wattage	Lumens (lm)	CCT (K)	Beam Angle (°)
	S9525/92TC/WH	240	12	850/1000/950	2700/4000/6000	36
	S9525MP125TC/WH	240	15/20/25	2300/2650/2650	2700/4000/6000	36
	S9525MP145TC/WH	240	25/30/35	3350/3700/3750	2700/4000/6000	36

Model No.	Dimmable	CRI	Body Colour	Cut Out (mm)	Diameter (mm)	Dim (mm)
S9525/92TC/WH	YES	90	WHITE	92	105	72(H)
S9525MP125TC/WH	NO	90	WHITE	125	140	115(H)
S9525MP145TC/WH	NO	90	WHITE	145	163	130(H)

Note: Lumens displayed are at maximum power

Due to continued product and technology enhancements, data sourced from sal.net.au shall not form part of any contract and or technical performance guarantee unless expressly confirmed in writing by SAL at the time of order. Products are sold in accordance with [SAL Terms and Conditions of sale](#) and all images shown are for illustration purposes only and may vary from the actual colour or finish. Unless specifically stated, all IP ratings nominated for Interior products are from "below the ceiling".

Dimensions

