



## POPPI S9041R/TC2 - 9W

9 watt dimmable LED downlight, CRI80, with selectable CCT

### Application

Perfect for residential or commercial applications

### Design Specifications

- 9 watt remote flickerCONTROLLED dimmable driver, complete with flex & plug
- High efficiency LED optics, recessed low glare optical system
- Selectable CCT 3000K / 4000K / 5700K, CRI>80, 60° beam distribution
- Polyamide covered aluminium body profile with PC trim
- IC - 4 rated downlight and driver, double insulated
- IP54 from below the ceiling, IP40 above




### Performance

- Dimmable - **YES**
- Dimmer Type - **TRAILING EDGE**



### Technical Specification

Product	Model No.	Input Voltage (V/AC)	Power (W)	Lumens (lm)	CCT (K)	Beam Angle (°)
	S9041R/TC2WH	240	9	830/930/900	3000/4000/5700	60

Dimmable	CRI	Cut Out (mm)	Diameter (mm)	Dim (mm)
YES	80	92	100	55(H)

Due to continued product and technology enhancements, data sourced from sal.net.au shall not form part of any contract and or technical performance guarantee unless expressly confirmed in writing by SAL at the time of order. Products are sold in accordance with SAL Terms and Conditions of sale and all images shown are for illustration purposes only and may vary from the actual colour or finish. Unless specifically stated, all IP ratings nominated for Interior products are from "below the ceiling".