

SURFACE MOUNTED DIMMABLE LED DOWNLIGHT

S9046, S9048 SM ECOSTAR



CONSTRUCTION

- Pressed metal surface mount casing
- Powder coated finish
- S9046 or S9048 LED downlight kits included
- Built-in constant current trailing edge dimmable LED driver

IP RATING

- IP20 suitable for interior use only


DIMMING OPTIONS (S9046SM/C)

- 1-10V analogue
- DALI / DSI, digital

BEAM ANGLE OPTIONS (S9046SM/C)

- 40° beam angle reflector

DIMENSIONS



Model No.	Input	Power	Lumen	CCT	Beam Angle	CRI	Dimmable	Fitting Colour
S9046SM/C WW WH	240V	9W	800lm	3000K	60°	>82	Yes*	White
S9046SM/C DL WH	240V	9W	850lm	6000K	60°	>80	Yes*	White

*Trailing edge dimming

Model No.	Input	Power	Lumen	CCT	Beam Angle	CRI	Dimmable	Fitting Colour
S9048SM/C WW WH	240V	12W	750lm	3000K	55°	>80	Yes*	White
S9048SM/C DL WH	240V	12W	800lm	5000K	55°	>80	Yes*	White

*Trailing edge dimming

PHOTOMETRIC DATA

Please refer to S9046, S9048



Specifications above are for reference only and may vary without prior notice