




DIMMABLE LED DOWNLIGHT

S9145, S9146 ECOSTAR II



DIMENSIONS



CONSTRUCTION

- Die-cast aluminium body
- Powder coated finish
- High output COB LED chip
- Changeable multi-reflector system
- Polycarbonate optical lens
- Constant current trailing edge dimmable LED driver fitted
- 1.2 m flex & 2 pin plug fitted

IP RATING

- IP20 suitable for interior use only

DIMMING OPTIONS

- 1-10V analogue
- DALI / DSI, digital




BEAM ANGLE

- 60° (standard)
- 25° reflector (option)
- 40° reflector (option)

Model No.	Input	Power	Lumen	CCT	Beam Angle	CRI	Dimmable	Fitting Colour
S9145WW/WH	240V	9W	700lm	3000K	60°	>80	Yes*	White
S9145CW/WH	240V	9W	800lm	4000K	60°	>80	Yes*	White
S9145DL/WH	240V	9W	800lm	6000K	60°	>80	Yes*	White
S9146WW/WH	240V	9W	700lm	3000K	60°	>80	Yes*	White
S9146CW/WH	240V	9W	800lm	4000K	60°	>80	Yes*	White
S9146DL/WH	240V	9W	800lm	6000K	60°	>80	Yes*	White

*Trailing edge dimming

PHOTOMETRIC DATA Unit: cd C0/C180 — C90/C270



Dimmer / Switch
Compatible



www.sal.net.au