

# LED CLEANROOM PANEL



## S9714-CR BISMARCK



### DIMENSIONS

S606FMCR  L x W: 636 x 636 mm

S312FMCR  L x W: 1206 x 336 mm



### CONSTRUCTION

- Fully enclosed and sealed plaster troffer frame
- Adjustable flip-out mounting brackets on two sides
- Pressed steel frame
- Powder coated finish

- Purposely sealed shockproof clear polycarbonate lens
- 1.5 m flex & 3 pin plug fitted

### IP RATING

- IP65 weatherproof front only

### CLEAN ROOM PANELS

Model No.	Input	Power	Lumen	CCT	Beam Angle	CRI	Fitting Colour	Dimensions L x W x H
S9714/606CR/CW	240V	30W	3200lm	4000K	100°	>80	White	656 x 656 x 108 mm
S9714/606CR/DL	240V	30W	3300lm	6000K	100°	>80	White	656 x 656 x 108 mm
S9714HC/606CR/CW	240V	40W	3200lm	4000K	100°	>95	White	656 x 656 x 108 mm
S9714/606CR/TC	240V	30W	3100lm/3200lm/3300lm	3000K/4000K/5700K	100°	>80	White	656 x 656 x 108 mm
S9714HO/606CR/TC	240V	40W	3700lm/ 4200lm/ 4000lm	3000K/4000K/5700K	100°	>80	White	656 x 656 x 108 mm
S9714/312CR/CW	240V	30W	3100lm	4000K	100°	>80	White	1236 x 336 x 108 mm
S9714/312CR/DL	240V	30W	3200lm	6000K	100°	>80	White	1236 x 336 x 108 mm
S9714HC/312CR/CW	240V	40W	2800lm	4000K	100°	>95	White	1236 x 336 x 108 mm
S9714/312CR/TC	240V	30W	3100lm/3200lm/3300lm	3000K/4000K/5700K	100°	>80	White	1236 x 336 x 108 mm
S9714HO/312CR/TC	240V	40W	3600lm/ 4000lm/ 3800lm	3000K/4000K/5700K	100°	>80	White	1236 x 336 x 108 mm

