

# FIRE RATED DIMMABLE LED DOWNLIGHT

## S9902F-S9053 FIREFOX



### CONSTRUCTION

- Steel canister with anti-fire insulation
- Robust constructions, powder coated finish
- Fire rated: 120 mins
- Compliant with Australian standard AS1530.4
- S9053 LED module fitted
- Constant current trailing edge dimmable LED driver fitted

### IP RATING

- IP20 suitable for interior use only

### DIMMING OPTIONS

- 1-10V analogue
- DALI / DSI, digital

### BEAM ANGLE

- 60° (standard)
- 25° reflector (option)
- 40° reflector (option)





### DIMENSIONS



Ø 85 mm

In the event of ceiling fire, the rise in temperature causes the insulation in the can to expand and thus closes the fitting ventilation holes, preventing the spread of fire between ceiling void and room.




Model No.	Input	Power	Lumen	CCT	Beam Angle	CRI	Dimmable	Fitting Colour
S9902F/120-S9053 WP	240V	9W	700lm	3000K	60°	>80	Yes*	White
S9902F/120-S9053 CP	240V	9W	800lm	4000K	60°	>80	Yes*	White
S9902F/120-S9053 DP	240V	9W	800lm	6000K	60°	>80	Yes*	White

\*Trailing edge dimming


### PHOTOMETRIC DATA

Unit: cd C0/C180 — C90/C270

S9902F-S9053 WP



S9902F-S9053 CP



S9902F-S9053 DP

