



## SALRAY 1500 FLEXI - SSPF1500

IP65 LED SOLAR floodlight - 1500 lumens, remote solar panel

### Application

A sustainable floodlight solution for residential exterior spaces

### Design Specifications

- Robust ABS body, PC visor and a versatile angled bracket for easy installation. Remote solar panel system, maximum 3 metre lead supplied.
- High efficiency LED optics, 1500 lumens, CRI >70, CCT 5000K, non-dimmable integral driver, beam distribution 110°
- Lithium battery technology, with overcharge, over-discharge, load short circuit protection
- Microwave and dusk to dawn control
- Detection range 110°, max 8m, installation height 3-5hm, hold time 30 sec, charge time 4 hours full sun
- **Remote control included, four function modes available - MODE 2 (Dusk to Dawn applied)** - default factory setting (no controller required): When there is no movement identified in the detection zone, the light output remains at 10%. When movement is identified in the detection zone, the light returns to 60% charged output. **MODE 1 (Dusk to Dawn applied)** - SAL remote control required: When there is no movement identified in the detection zone, the light turns OFF, When movement is identified in the detection zone, the light will turn ON to its maximum charge. **MODE 3 (Sensor override applied)** - SAL remote control required: The light remains at 35% output, (PIR sensor function is disabled). 5 hour operation when fully charged **MODE 4 (Sensor override applied)** - SAL remote control required: The light remains at 20% output, (Microwave sensor function is disabled). 6 hour operation when fully charged.



### Performance

- Dimmable - **NO**
- In Built Sensor - **YES**
- Sensor Type - **Microwave**



## Technical Specification

Product	Model No.	Power (W)	Lumens (lm)	CCT (K)	CRI	Beam Angle (°)
	SSPF1500	10	1500	5000	70	110
	SSPF/RC INCL.					
Body Colour	Dim (mm)		Mass (kg)			
BLACK	233(L) x 50(W) x 200(H)		2.5			
BLACK	85(L) x 40(W) x 5(D)		0.01			

Due to continued product and technology enhancements, data sourced from sal.net.au shall not form part of any contract and or technical performance guarantee unless expressly confirmed in writing by SAL at the time of order. Products are sold in accordance with [SAL Terms and Conditions of sale](#) and all images shown are for illustration purposes only and may vary from the actual colour or finish. Unless specifically stated, all IP ratings nominated for Interior products are from "below the ceiling".

## Dimensions

