



SALRAY 6000 FLEXI - SSPF6000

IP65 LED SOLAR floodlight - 6000 lumens, remote solar panel

Application

A sustainable floodlight solution for residential or commercial exterior spaces

Design Specifications

- Robust ABS body, PC visor and a versatile angled bracket for easy installation. Remote solar panel system, maximum 6 metre system lead supplied, panel mounting brackets (if required) are ordered separately, SSPF6/9PV/INSKIT.
- High efficiency LED optics, 6000 lumens, CRI >70, CCT 5000K, non-dimmable integral driver, beam distribution 110°
- Lithium battery technology, with overcharge, over-discharge, load short circuit protection
- Dusk to dawn control
- Charge time 4 hours full sun
- **Remote control included, four function modes available** - refer installation instructions for settings.



Performance

- Dimmable - **NO**



Technical Specification

Product	Model No.	Power (W)	Lumens (lm)	CCT (K)	CRI	Beam Angle (°)
	SSPF6000	40	6000	5000	70	110
	SSPF/RC INCL.					



Body Colour	Dim (mm)	Mass (kg)
BLACK	330(L) x 56(W) x 294(H)	
BLACK	85(L) x 40(W) x 5(D)	0.01

Due to continued product and technology enhancements, data sourced from sal.net.au shall not form part of any contract and or technical performance guarantee unless expressly confirmed in writing by SAL at the time of order. Products are sold in accordance with [SAL Terms and Conditions of sale](#) and all images shown are for illustration purposes only and may vary from the actual colour or finish. Unless specifically stated, all IP ratings nominated for Interior products are from "below the ceiling".