



# LED OYSTER LIGHT

## SO3700 OPAL



### DIMENSIONS



### CONSTRUCTION

- Powder coated steel base
- Opal polycarbonate diffuser
- High efficiency SMD LED chips
- Constant current non-dimmable LED driver fitted
- Select colour temperature with DIP switch (TC models)

### DIMMING OPTIONS

- Trailing edge
- 1-10V analogue (SO3700/40L only)
- DALI / DSI, digital (SO3700/40L only)

### IP RATING

- IP20 suitable for interior use only

### SENSOR OPTION

- Integrated microwave motion sensor (SO3700/40L only)

Model No.	Input	Power	Lumen	CCT	CRI	Dimensions Ø x H
SO3700/30L TC	240V	18W	1400lm/1500lm/1500lm	3000K/4000K/6000K	>80	310 x 100 mm
SO3700/40L TC	240V	30W	2500lm/2600lm/2600lm	3000K/4000K/6000K	>80	390 x 112 mm

### SO3700: DAYLIGHT OPTION AVAILABLE

Model No.	Input	Power	Lumen	CCT	CRI	Dimensions Ø x H
SO3700/30L DL	240V	18W	1600lm	6000K	>80	310 x 100 mm
SO3700/40L DL	240V	30W	2700lm	6000K	>80	390 x 112 mm