



TUBELINE BARE STB - 9/36W

Conventional LED bare battens 9-36 watt

Application

Conventional designed LED surface mount battens, ideal for most commercial interior service spaces

Design Specifications

- Pressed steel base with PVC body dimensions LWH: (9W) 625 x 55 x 77mm, (18W) 1225 x 55 x 77mm, (2x9w) 625 x 100 x 77mm, (2x18W) 1225 x 100 x 77mm
- Large terminal block, easy installation, 9, 18, 2 x 9, 2 x 18 watt models
- Quality white powder coat finish
- High efficiency LED T8 tubes fitted, CRI > 80, CCT 4000, 5000, 6000K
- Safety fuse installed
- Optional sensor models , wire guard (STG series) and emergency models with LiFePO4 battery technology compliant to AS/NZS2293 are available



Performance

In Built Sensor - **OPTIONAL**

Sensor Type - **MICROWAVE**

Technical Specification

Model No.	Description	Input Voltage (V/AC)	Lumens (lm)	Power (W)	CCT (K)	CRI
STB/112 CW	LED BATTEN 18W	240	1600	18	4000	80
STB/112 DL	LED BATTEN 18W	240	1700	18	5000	80
STB/206 CW	LED BATTEN 2 X 9W	240	1700	18	4000	80
STB/206EM2500	LED EMERG. BATTEN 2 X 9W 4K	240	1700	18	4000	80
STB/212 CW	LED BATTEN 2 X 18W	240	3200	36	4000	80
STB/212 DL	LED BATTEN 2 X 18W	240	3400	36	6000	80
STB/212EM2500	LED EMERG. BATTEN 2 X 18W 4K	240	3200	36	4000	80

Technical Specification

Model No.	Beam Angle (°)	Body Colour	Dim (mm)
STB/112 CW	120	WHITE	1225(L) x 55(W) x 77(H)
STB/112 DL	120	WHITE	1225(L) x 55(W) x 77(H)
STB/206 CW	120	WHITE	625(L) x 100(W) x 77(H)
STB/206EM2500	120	WHITE	625(L) x 100(W) x 77(H)
STB/212 CW	120	WHITE	1225(L) x 100(W) x 77(H)
STB/212 DL	120	WHITE	1225(L) x 100(W) x 77(H)
STB/212EM2500	120	WHITE	1225(L) x 100(W) x 77(H)

STB/206EM2500, STB/212EM2500 TUBELINE, Compliant to AS2293, LED charge status indicator, Test switch, Guaranteed 90 minutes emergency operation, Intelligent automatic recharging function, 16 hours charge time, Deep discharge protection, SELV compliant

Due to continued product and technology enhancements, data sourced from sal.net.au shall not form part of any contract and or technical performance guarantee unless expressly confirmed in writing by SAL at the time of order. Products are sold in accordance with [SAL Terms and Conditions of sale](#) and all images shown are for illustration purposes only and may vary from the actual colour or finish. Unless specifically stated, all IP ratings nominated for Interior products are from "below the ceiling".

Product Images

