



TUBELINE DIFFUSE STD - 9/36W

Conventional LED tube diffuse battens 9 - 36 watt

Application

Conventional LED interior battens ideal for residential and commercial service spaces

Design Specifications

- Pressed steel base with PVC body
- Large terminal block, easy installation
- Quality white powder coat finish
- High efficiency LED T8 tubes fitted, beam distribution 120 degree, CRI >80, 3000K, 4000K, 6000K
- Safety HRC fuse installed
- Optional sensor models , wire guard (STG series) and emergency models with LiFePO4 battery technology compliant to AS/NZS2293 are available. Battery warranty twelve (12) months

Performance

In Built Sensor - **OPTIONAL**
Sensor Type - **MICROWAVE**





Technical Specification

Model No.	Description	Input Voltage (V/AC)	Lumens (lm)	Power (W)	CCT (K)	CRI
STD/106 WW	LED DIFF. BAT. 9W	240	650	9	3000	80
STD/106 CW	LED DIFF. BAT. 9W	240	700	9	4000	80
STD/106 DL	LED DIFF. BAT. 9W	240	750	9	6000	80
STD/112 WW	LED DIFF. BAT. 18W	240	1300	18	3000	80
STD/112 CW	LED DIFF. BAT. 18W	240	1400	18	4000	80
STD/112 DL	LED DIFF. BAT. 18W	240	1700	18	6000	80
STD/206 WW	LED DIFF. BAT. 2 X 9W	240	1400	18	3000	80
STD/206 CW	LED DIFF. BAT. 2 X 9W	240	1400	18	4000	80
STD/206 DL	LED DIFF. BAT. 2 X 9W	240	1500	18	6000	80
STD/212 WW	LED DIFF. BAT. TWIN	240	2600	36	3000	80
STD/212 CW	LED DIFF. BAT. TWIN	240	2800	36	4000	80
STD/212 DL	LED DIFF. BAT. TWIN	240	3000	36	6000	80
STD/206EM2500	LED EMERG. BATTEN 2 X 9W 4K	240	n/a	18	4000	80
STD/212EM2500	LED EMERG. DIFF. BAT. TWIN 4K	240	n/a	36	4000	80

Technical Specification

Model No.	Beam Angle (°)	Dimmable	Body Colour	Dim (mm)
STD/106 WW	120	NO	WHITE	625(L) x 65(W) x 77(H)
STD/106 CW	120	NO	WHITE	625(L) x 55(W) x 77(H)
STD/106 DL	120	NO	WHITE	625(L) x 55(W) x 77(H)
STD/112 WW	120	NO	WHITE	1225(L) x 55(W) x 77(H)
STD/112 CW	120	NO	WHITE	1225(L) x 55(W) x 77(H)
STD/112 DL	120	NO	WHITE	1225(L) x 55(W) x 77(H)
STD/206 WW	120	NO	WHITE	625(L) x 110(W) x 77(H)
STD/206 CW	120	NO	WHITE	625(L) x 110(W) x 77(H)
STD/206 DL	120	NO	WHITE	625(L) x 110(W) x 77(H)
STD/212 WW	120	NO	WHITE	1225(L) x 110(W) x 77(H)
STD/212 CW	120	NO	WHITE	1225(L) x 110(W) x 77(H)
STD/212 DL	120	NO	WHITE	1225(L) x 110(W) x 77(H)
STD/206EM2500	120	NO	WHITE	625(L) x 110(W) x 77(H)
STD/212EM2500	120	NO	WHITE	1225(L) x 110(W) x 77(H)

Note: D50 emergency classification

Due to continued product and technology enhancements, data sourced from sal.net.au shall not form part of any contract and or technical performance guarantee unless expressly confirmed in writing by SAL at the time of order. Products are sold in accordance with [SAL Terms and Conditions of sale](#) and all images shown are for illustration purposes only and may vary from the actual colour or finish. Unless specifically stated, all IP ratings nominated for Interior products are from "below the ceiling".

Dimensions

