



UFO II SHB25HE - 80/180W

UFO II 80 - 180 watt IP65 LED multi function highbay or floodlight, with optional quick connect sensor

Application

Low profile 1-10V dimmable LED highbay, ideal for commercial or industrial warehouse installations

Design Specifications

- Stylish die-cast aluminium body, complete with safety lanyard
- Quick connect plug and play with step dimming and optional sensor available
- High efficiency SMD LED chips, with an impressive 150lm/W optical performance, CCT 5700K, CRI > 80
- 120 degree beam distribution, polycarbonate diffuser
- Integral 1-10v dimmable LED driver with 4KV surge protection, IP65, IK08 rated, complete with flex and plug for easy installation
- Multi function lowbay, floodlight and metallic reflector accessories available



Performance

Dimmable Driver - **YES**
 Dimmer Type - **1-10V**
 In Built Sensor - **OPTIONAL**
 Sensor Type - **MICRO**

Technical Specification

Model No.	Description	Input (V)	Power (W)	Lumens (lm)	CCT (K)	Beam Angle (°)
SHB25HE80	LED HIGHBAY 80W 5700K	240	80	12000	5700	120
SHB25HES80	LED HIGHBAY 80W 5700K SENSOR	240	80	12000	5700	120
SHB25HE120	LED HIGHBAY 120W 5700K	240	120	18000	5700	120
SHB25HES120	LED HIGHBAY 120W 5700K SENSOR	240	120	18000	5700	120
SHB25HE180	LED HIGHBAY 180W 5700K	240	180	27000	5700	120
SHB25HES180	LED HIGHBAY 180W 5700K SENSOR	240	180	27000	5700	120



Model No.	CRI	Body Colour	Mass (kg)
SHB25HE80	80	BLACK	3.25
SHB25HES80	80	BLACK	3.25
SHB25HE120	80	BLACK	3.5
SHB25HES120	80	BLACK	3.5
SHB25HE180	80	BLACK	3.92
SHB25HES180	80	BLACK	3.92

Due to continued product and technology enhancements, data sourced from sal.net.au shall not form part of any contract and or technical performance guarantee unless expressly confirmed in writing by SAL at the time of order. Products are sold in accordance with [SAL Terms and Conditions of sale](#) and all images shown are for illustration purposes only and may vary from the actual colour or finish.

Product Images

