



WARRAGUL - STR4884MPXTC 15/35W

Decorative three circuit, rotatable LED track light, with selectable CCT and power.

Application

Designed for decorative residential, retail and commercial applications

Design Specifications

- Aluminium profile, horizontal 355° rotation, 90° vertical tilt
- Choice of white or black powder coated finish
- High performance LED optics, CRI>90
- CCT selectable 2700K / 4000K / 6000K
- Beam distribution 36°
- Integral non-dimmable flicker CONTROLLED gear with selectable power 15/20/25W, 25/30/35W



Performance

- Dimmable - NO



Technical Specification

Product	Model No.	Input Voltage (V/AC)	Multiple Wattage	Lumens (lm)	CCT (K)	Body Colour
	STR4884MP25TC/WH	240	15/20/25	2700/3100/3000	2700/4000/6000	WHITE
	STR4884MP25TC/BK	240	15/20/25	2500/2900/2800	2700/4000/6000	BLACK
	STR4884MP35TC/WH	240	25/30/35	3600/3900/3800	2700/4000/6000	WHITE
	STR4884MP35TC/BK	240	25/30/35	3200/3500/3400	2700/4000/6000	BLACK

CRI	Beam Angle (°)	Dimmable	Dim (mm)
90	36	NO	170(L) x 75(W) x 220(H)
90	36	NO	170(L) x 75(W) x 220(H)
90	36	NO	170(L) x 85(W) x 210(H)
90	36	NO	170(L) x 85(W) x 210(H)

Note: Lumens (lm) displayed are at the maximum power selection.

NOTE: tracklight systems are designed for horizontal ceiling mount, with the track opening parallel to the floor, for non-raked ceiling installations

Due to continued product and technology enhancements, data sourced from sal.net.au shall not form part of any contract and or technical performance guarantee unless expressly confirmed in writing by SAL at the time of order. Products are sold in accordance with [SAL Terms and Conditions of sale](#) and all images shown are for illustration purposes only and may vary from the actual colour or finish. Unless specifically stated, all IP ratings nominated for Interior products are from "below the ceiling".

Dimensions

