



## ITEM NO:21242

## Parts and Hardware List

A.	Top Cover	1PC
B.	Lamp body	1PC
C.	Glass Shade	6PCS
D.	Cross Bar	1PC
E.	Outlet Box Screws	2pcs
F.	Pre-Threaded Pipe	1PC
G.	Hex Nut	2PCS
H.	Pre-Threaded Ring	1PC
I.	Collar Loop	1PC
J.	Canopy	1PC
K.	Wire Nut	3PCS
L.	Chain	1PC
M.	Quick Link	2PCS
N.	Suspenders	2PCS
O.	Socket Ring	6PCS
P.	Green Ground Screw	

Please make sure that you have all the parts indicated before you begin assembly of this item

Please read Wiring Instructions before you begin assembling and installing your Chandelier

### Assembly Instructions

- Carefully remove the parts and hardware from the carton.
- Attach the Lamp body(B) to the Top Cover(A) by Suspenders(N). See Illustration.
- Fasten the Cross Bar (D) to the outlet box using the Outlet Box Screws(E).
- Insert the shorter end of the Pre-Threaded Pipe (F) into the pre-drilled hole in the Cross Bar(D) and secure with the Hex Nut(G).See Illustration.
- Attach the Collar Loop (I) to the exposed end of the Pre-Threaded Pipe (F) and secure by turning in a clockwise direction.
- Attach the Quick Links(M) to two bitter end of the Chain(L)
- Attach the Quick Link(M) on one end of the Chain to the loop on the Top Cover(A)
- Slip the Pre-Threaded Ring(H) first and then the Canopy (J) over the other end of the Chain (L),then Attach the Adjustable Link on other end of the Chain to Collar Loop(I).
- Lace the wire through every link of the chain,through the collar and up through the Pre-Threaded Pipe(F) See Illustration.
- Place the white ,ribbed or tinted wire evenly against the white wire from the outlet box and place the black,smooth or un-tinted wire evenly against the black wirt from the outlet box.(Connecting the Wire-See Figure2)
- Install the ground wire in the Cross Bar(D) with the Geen Ground Screw(P) supplied.
- After the wires are connected ,tuck them carefully inside the outlet box. Place Canopy(I)over the outlet box and secure with Pre-Threaded Ring(H)
- Attach the Glass Shade (C) onto the socket of Lamp Body (B) and secure by turning in a clockwise direction. See Illustration.
- Attach the Socket Ring (O) onto the Glass Shade (C) and fix it onto the socket of Lamp Body(B) securely by turning in a clockwise direction. See Illustration.
- Install 60 Watt,Type A bulbs(sold separately)into the sockets of the fixture.



## Illustration

STYLE NO.:21242

**CLEANING:** This item has a lacquered and baked finish. When cleaning only use a soft, dry cloth. Do not use liquid cleansers or abrasives as they may damage the finish.

